

FORTADOR PRO ELECTRA

TECHNICAL SPECIFICATIONS

Maximum working steam pressure	16 BAR (232 PSI)
Steam operating temperature	120-140°C or 234-273°F
Boiler temperature	max. 260°C or 506°F thermostat / auto stop
Number of boilers	1
Total capacity of boilers	14,5 l (4 gal)
Preheating time	2-7 min
Tank capacity: water / det. 1	20 l (5 gal) / 5 l (1,3 gal)
Operating volume	60-78 dB
Voltage and frequency	380-400 V / 50-60 Hz

Net weight	95 kg or 209 lb
Dimensions	50 cm(20 in) W x 86 cm (34 in) L x 91 cm (36 in) H
Casing material	Aluminium
Boiler material	Boiler steel
Chemical-free descaling system	YES
Hot detergent feeding	YES
Emergency button STOP	YES
Shock protection	YES
Work on water tanks or direct connection from a garden hose	YES
Power consumption (W)	11 kW

LCD 7" touchscreen display – functions

- Pressure gauge;
- Fluids level indicator;
- Working hours meter;
- Serial number display;
- Information about the water level in the boiler;
- Information about the operation of the water pump and heaters;
- Setting dry or wet steam;
- Service panel;
- Water removal to prevent it from freezing;
- Launching the detergent feed from the machine.

Additional accessories

- Anti-burn steam gun RL20: 2 pcs.
- Insulated pressure steam hose (10 m / 30 ft.): 2 pcs.
- Short lance with variable spacing steam nozzle (50 cm / 20 in): 1 pc.
- Transport belts: 2 pcs.
- Repair kit: 1 pc.