

FORTADOR SENSORY 32A

TECHNICAL SPECIFICATIONS



Maximum working steam pressure	16 bar (232 PSI)
Steam operating temperature	110–135 °C (230–275 °F)
Boiler temperature	250–270 °C (482–518 °F)
Number of boilers	1
Total boiler capacity	10 l
Preheating time	3–5 min
Water tank capacity	10 l
Detergent tank	–
Power supply	400 V / 50–60 Hz (3 ~)
Required protection	32 A (minimum)
Power consumption	9,0 kW
Heating system	High efficiency electric boiler
Hot detergent feeding	NO
Direct water connection	YES
Continuous working time	Unlimited (with water feed)
Net weight	67 kg
Dimensions (L x W x H)	77 cm x 40 cm x 88 cm (30.3 in x 15.7 in x 34.6 in)
Case material	Aluminium
Boiler material	Stainless steel (AISI 304)
STOP emergency button	YES
Shock protection	YES
Water level sensor	YES
Chemical-free descaling system	YES
Work with water tanks or direct connection	YES
Power cable length	5 m
Noise level	< 70 dB
Mobility	4 wheels (2 lockable)

LCD 7" touchscreen display – functions

- Pressure display
- Real-time temperature
- Working hours counter
- Service reminders
- Information about maintenance
- Selection of 9 preset programs
- Information about system status
- Error diagnostics
- Multilanguage menu
- Child lock
- Software updates via USB
- Intuitive and easy operation

Standard accessories

- Full gun & hose set (2 units – 10 m or 33 ft)
- Twister nozzle
- Set of nozzles for upholstery, detailing & disinfection
- Steam mop
- Maintenance technical set
- Fortador bag

Optional accessories

- Steam mop for glass and solar panels
- Steam mop microfiber pads
- Set of brushes and scrapers
- Extension hoses (10 m / 33 ft)
- Teflon steam nozzle